3888

TEMOTO



## Electronic Temperature Controller Product Line

Tempro electronic temperature controllers are designed to accurately regulate precise temperature in commercial, industrial and agricultural settings.

- Higher accuracy of temperature regulation compared to mechanical thermostats.
- Single and dual stage models available.
- Adjustable temperature ranges.
- Adjustable differential temperature range.
- Easy to read LED display.
- User changeable display from Celsius and Fahrenheit
- LED power indicator lamp
- Multiple conduit knockouts to give flexibility to the installer.
- Other custom options available such as custom sensor lengths, cycle timer, defrost function and piggyback plug.

Flip for complete fact sheet.



www.tempro-products.com

Manufactured by Senasys Inc., 1435 International Drive, Eau Claire, WI 54701 Phone: 715-831-6353 | Email: info@senasys.com

- Durable NEMA 4X Rated
  Enclosure
  - Accurate Air And Fluid Temperature Regulation
- Units Available For Heating
  And Cooling



| тетбго                                                 | Electronic Temperature Controller         |                                                        | Product Specifications                    |                                           |  |
|--------------------------------------------------------|-------------------------------------------|--------------------------------------------------------|-------------------------------------------|-------------------------------------------|--|
|                                                        | DSD601AD                                  | DSD602AD                                               | DSD603AD                                  | DSD701AD                                  |  |
| Basic Construction                                     | Polymeric NEMA 4X                         | Polymeric NEMA 4X                                      | Polymeric NEMA 4X                         | Polymeric NEMA 4X                         |  |
|                                                        | Rated Housing                             | Rated Housing                                          | Rated Housing                             | Rated Housing                             |  |
| Function                                               | Heat & Cool                               | Heat & Cool                                            | Heat & Cool                               | Heat & Cool                               |  |
| Switch Type                                            | Single Stage,                             | Single Stage,                                          | Single Stage,                             | Two Stage,                                |  |
|                                                        | SPDT                                      | SPDT                                                   | SPDT                                      | SPDT/SPDT                                 |  |
| Temperature Range                                      | -30°F to 220°F                            | -30°F to 250°F                                         | 200°F to 500°F                            | -30°F to 220°F                            |  |
| Additional Features                                    | 8-ft NTC Sensor, Adj.<br>Diff. 1º to 30ºF | 8-ft NTC Sensor, Adj.<br>Diff. 1º to 30ºF              | 8-ft NTC Sensor, Adj.<br>Diff. 1º to 30ºF | 8-ft NTC Sensor, Adj.<br>Diff. 1º to 30ºF |  |
| UL Listed<br>UL Listed to Canadian Safety<br>Standards | ~                                         | ~                                                      | ~                                         | $\checkmark$                              |  |
| Electrical Ratings                                     |                                           |                                                        |                                           |                                           |  |
| 120V/240V/277V AC                                      |                                           |                                                        |                                           |                                           |  |
| Resistive                                              | 30A                                       | 30A                                                    | 30A                                       | 30A                                       |  |
| Inductive                                              | 96A                                       | 96A                                                    | 96A                                       | 96A                                       |  |
| Locked Rotor                                           | 30A                                       | 30A                                                    | 30A                                       | 30A                                       |  |
| Unit Carton                                            |                                           |                                                        |                                           |                                           |  |
| Length (in.)                                           | 7.08                                      | 7.08                                                   | 7.08                                      | 7.08                                      |  |
| Width (in.)                                            | 2.68                                      | 2.68                                                   | 2.68                                      | 2.68                                      |  |
| Depth (in.)                                            | 2.56                                      | 2.56                                                   | 2.56                                      | 2.56                                      |  |
| Master Pack                                            |                                           |                                                        |                                           |                                           |  |
| Quantity per Master Pack                               | 40                                        | 40                                                     | 40                                        | 40                                        |  |
| Length (in.)                                           | 16.56                                     | 16.56                                                  | 16.56                                     | 16.56                                     |  |
| Width (in.)                                            | 13.07                                     | 13.07                                                  | 13.07                                     | 13.07                                     |  |
| Height (in.)                                           | 14.37                                     | 14.37                                                  | 14.37                                     | 14.37                                     |  |
| Weight Per Pack (Lbs)                                  | 23                                        | 23                                                     | 23                                        | 23                                        |  |
|                                                        | The housings of all unit                  | The housings of all units are 5.72"L x 2.49"W x 2.09"D |                                           |                                           |  |



**TEMÕſO**<sup>™</sup> www.tempro-products.com

Manufactured by Senasys Inc., 1435 International Drive, Eau Claire, WI 54701 Phone: 715-831-6353 | Email: info@senasys.com